

Alto 258

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Length (cm)** 32
- **Thickness (mm)** 0.60
- **Colour/Color** Yellow
- **Wrist** Straight cuff
- **Size** 6 7 8 9 10
- **Packaging** pair/bag - pairs/box - pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



2120



Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Blade cut resistance
 └─ Abrasion resistance
 └─ Puncture resistance
 └─ Tear resistance



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Burning behaviour
 └─ Contact heat resistance
 └─ Convective heat resistance
 └─ Radiant heat resistant
 └─ Resistance to small drops of molten metal
 └─ Resistance to large quantities of molten metal



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**RADIOACTIVE
CONTAMINATION
EN 421**



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Convective cold resistance
 └─ Contact cold resistance
 └─ Water permeability

For more details: www.mapa-pro.com

SPECIFIC ADVANTAGES

- Added comfort and absorption of perspiration, due to the cotton flock-lining
- Good handling of slippery objects, due to the embossed texture
- Good resistance to many diluted acids

MAIN FIELDS OF USE

Aeronautics industry

- Work with composite materials (resins)

Mechanical industry

- Assembly of small, oil and grease free parts
- Minor maintenance Tasks

Chemical industry

- Common handling Tasks

INSTRUCTIONS FOR USE

Instructions for use

- For enhanced safety and service life of the gloves :
- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitised to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with a solvent (alcohol, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : inappropriate usage of the gloves or submitting them to a cleaning or laundering process which is not specifically recommended, can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- CE-Type Examination Certificate 0072/014/162/05/94/10513
- Issued by the notified body nr 0072
I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX
- Quality assurance certificat 0334 Asqual 14 rue des Reculettes -F-75013 PARIS