

**Regain Floor****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Regain Floor  
Product code : 110540E  
Use of the Substance/Mixture : Floor Cleaner  
Substance type: : Mixture

**For professional users only.**

Product dilution information : No dilution information provided.

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Floor cleaner. Manual process  
Recommended restrictions on use : Reserved for industrial and professional use.

**1.3 Details of the supplier of the safety data sheet**

Company : Ecolab Ltd.  
PO Box 11; Winnington Avenue  
Northwich, Cheshire, United Kingdom CW8 4DX  
+ 44 (0)1606 74488  
ccs@ecolab.com

**1.4 Emergency telephone number**

Emergency telephone number : Food & Beverage, Institutional, Agriculture, Textile Hygiene:  
Northwich: +44 (0)1606 74488  
Healthcare Leeds: +44 (0)113 232 2480  
Healthcare Swansea: +44 (0)1235 239670  
Poison Information Centre telephone number : Not Available

Date of Compilation/Revision : 23.05.2016  
version : 1.0

**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Skin corrosion, Category 1A	H314
Serious eye damage, Category 1	H318
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335

**Regain Floor**


The classification of this product is based only on its extreme pH value (in accordance with current European legislation).

**Classification (67/548/EEC, 1999/45/EC)**

C; CORROSIVE  
 The classification of this product is based only on its extreme pH value (in accordance with current European legislation).  
 R35  
 R37

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.  
 H335 May cause respiratory irritation.

Precautionary Statements : **Prevention:**  
 P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:  
 monoethanolamine

**2.3 Other hazards**

None known.

**Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2 Mixtures**

**Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	ClassificationREGULATION (EC) No 1272/2008	Concentration: [%]
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318	>= 5 - < 10

**Regain Floor**

Fattyalcohol ethoxylates > 5EO	69227-22-1	Acute toxicity Category 4; H332 Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6	Eye irritation Category 2; H319	>= 5 - < 10
fatty acids, coco, compds. with ethanolamine	66071-80-5 266-105-0	Serious eye damage Category 2; H319 Skin irritation Category 2; H315	>= 5 - < 10
potassium carbonate	584-08-7 209-529-3 01-2119532646-36	Acute toxicity Category 4; H302 Eye irritation Category 2; H319 Skin corrosion/irritation Category 2; H315 Specific target organ toxicity - single exposure Category 3; H335	>= 3 - < 5
Fattyalcohol ethoxylates > 5EO	69011-36-5 500-241-6	Serious eye damage Category 1; H318	>= 2.5 - < 3
propan-2-ol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 2.5 - < 3
alcohols, c13-15-branched and linear, butoxylated ethoxylated	111905-53-4	Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 2.5 - < 3

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Indication of immediate medical attention and special treatment needed**

Treatment : Treat symptomatically.

**Section: 5. FIREFIGHTING MEASURES**

**5.1 Extinguishing media**

**Regain Floor**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Fire Hazard  
Keep away from heat and sources of ignition.  
Flash back possible over considerable distance.  
Beware of vapours accumulating to form explosive concentrations.  
Vapours can accumulate in low areas.

Hazardous combustion products : Decomposition products may include the following materials:  
Carbon oxides  
nitrogen oxides (NOx)  
Sulphur oxides  
Oxides of phosphorus

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

**Section: 6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel : Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**6.2 Environmental precautions**

Environmental precautions : Do not allow contact with soil, surface or ground water.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

**Regain Floor**

**6.4 Reference to other sections**

See Section 1 for emergency contact information.  
 For personal protection see section 8.  
 See Section 13 for additional waste treatment information.

**Section: 7. HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : -5 °C to 40 °C

**7.3 Specific end uses**

- Specific use(s) : Floor cleaner. Manual process

**Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
monoethanolamine	141-43-5	TWA	1 ppm 2.5 mg/m <sup>3</sup>	UKCOSSTD
Further information	Sk	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	3 ppm 7.6 mg/m <sup>3</sup>	UKCOSSTD
Further information	Sk	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67.5 mg/m <sup>3</sup>	UKCOSSTD
		STEL	15 ppm 101.2 mg/m <sup>3</sup>	UKCOSSTD
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m <sup>3</sup>	UKCOSSTD
		STEL	500 ppm 1,250 mg/m <sup>3</sup>	UKCOSSTD

**Regain Floor**

DNEL

2-(2-butoxyethoxy)ethanol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 101.2 mg/m3
		End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20 mg/kg
		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 67.5 mg/m3
		End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 67.5 mg/m3
propan-2-ol	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 888 mg/cm2
		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m3
		End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 319 mg/cm2
		End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3
		End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 26 ppm

PNEC

2-(2-butoxyethoxy)ethanol	:	Fresh water Value: 1 mg/l
		Marine water Value: 0.1 mg/l
		Intermittent use/release Value: 3.9 mg/l
		Sewage treatment plant

**Regain Floor**

		Value: 200 mg/l
		Sediment Value: 4 mg/kg
		Soil Value: 0.4 mg/kg
		Oral Value: 56 mg/kg
propan-2-ol	:	Fresh water Value: 140.9 mg/l
		Marine water Value: 140.9 mg/l
		Intermittent use/release Value: 140.9 mg/l
		Fresh water Value: 552 mg/kg
		Marine sediment Value: 552 mg/kg
		Soil Value: 28 mg/kg
		Sewage treatment plant Value: 2251 mg/l
		Oral Value: 160 mg/kg

**8.2 Exposure controls**

**Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

**Individual protection measures**

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles  
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection  
Gloves  
Nitrile rubber  
butyl-rubber  
Breakthrough time: 1 – 4 hours

**Regain Floor**

Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, 89/686/EEC ), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

**Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

**Section: 9. PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

Appearance : liquid

Colour : fluorescent, light green

Odour : alcohol-like

pH : 11.9 - 12.9, 100 %

Flash point : 58 °C closed cup, Does not sustain combustion.

Odour Threshold : Not applicable and/or not determined for the mixture

Melting point/freezing point : Not applicable and/or not determined for the mixture

Initial boiling point and boiling range : Not applicable and/or not determined for the mixture

Evaporation rate : Not applicable and/or not determined for the mixture

Flammability (solid, gas) : Not applicable and/or not determined for the mixture

Upper explosion limit : Not applicable and/or not determined for the mixture

Lower explosion limit : Not applicable and/or not determined for the mixture

Vapour pressure : Not applicable and/or not determined for the mixture

Relative vapour density : Not applicable and/or not determined for the mixture

Relative density : 1.023 - 1.033

Water solubility : soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture

Partition coefficient: n-octanol/water : Not applicable and/or not determined for the mixture

Auto-ignition temperature : Not applicable and/or not determined for the mixture

Thermal decomposition : Not applicable and/or not determined for the mixture



**Regain Floor**

Viscosity, kinematic : 24.363 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not applicable and/or not determined for the mixture

Oxidizing properties : The substance or mixture is not classified as oxidizing.

**9.2 Other information**

Not applicable and/or not determined for the mixture

**Section: 10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid**

Heat, flames and sparks.

**10.5 Incompatible materials**

None known.

**10.6 Hazardous decomposition products**

Decomposition products may include the following materials:  
Carbon oxides  
nitrogen oxides (NO<sub>x</sub>)  
Sulphur oxides  
Oxides of phosphorus

**Section: 11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

**Product**

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg

Acute inhalation toxicity : 4 h Acute toxicity estimate : > 5 mg/l

Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg

Skin corrosion/irritation : There is no data available for this product.

**Regain Floor**

Serious eye damage/eye irritation : There is no data available for this product.

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

**Components**

Acute oral toxicity : monoethanolamine  
LD50 rat: 1,089 mg/kg

Fattyalcohol ethoxylates > 5EO  
LD50 rat: > 2,000 mg/kg

2-(2-butoxyethoxy)ethanol  
LD50 rat: 3,306 mg/kg

potassium carbonate  
LD50 rat: 1,870 mg/kg

Fattyalcohol ethoxylates > 5EO  
LD50 rat: 4,380 mg/kg

propan-2-ol  
LD50 rat: 5,840 mg/kg

alcohols, c13-15-branched and linear, butoxylated ethoxylated  
LD50 rat: > 2,000 mg/kg

**Components**

Acute inhalation toxicity : monoethanolamine  
4 h LC50 rat: > 1.6 mg/l

Fattyalcohol ethoxylates > 5EO  
4 h LC50 rat: 3.5 mg/l

potassium carbonate  
4 h LC50 rat: > 5.26 mg/l

propan-2-ol  
4 h LC50 rat: > 30 mg/l

**Components**

**Regain Floor**

Acute dermal toxicity : monoethanolamine  
LD50 rabbit: 1,025 mg/kg

Fattyalcohol ethoxylates > 5EO  
LD50 rabbit: > 2,000 mg/kg

2-(2-butoxyethoxy)ethanol  
LD50 rabbit: 2,764 mg/kg

potassium carbonate  
LD50 rabbit: > 2,000 mg/kg

Fattyalcohol ethoxylates > 5EO  
LD50 rabbit: 2,150 mg/kg

propan-2-ol  
LD50 rabbit: 12,870 mg/kg

alcohols, c13-15-branched and linear, butoxylated ethoxylated  
LD50 rat: > 2,000 mg/kg

**Potential Health Effects**

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause respiratory tract irritation. May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

**Experience with human exposure**

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

**Section: 12. ECOLOGICAL INFORMATION**

**12.1 Ecotoxicity**

Environmental Effects : This product has no known ecotoxicological effects.

**Product**

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

**Components**

**Regain Floor**

Toxicity to fish : Fattyalcohol ethoxylates > 5EO  
96 h LC50 Fish: 5 mg/l

2-(2-butoxyethoxy)ethanol  
96 h LC50 Fish: 1,300 mg/l

potassium carbonate  
96 h LC50 Fish: 230 mg/l

propan-2-ol  
96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l

alcohols, c13-15-branched and linear, butoxylated ethoxylated  
96 h LC50 Fish: 5 mg/l

**Components**

Toxicity to daphnia and other aquatic invertebrates : monoethanolamine  
48 h EC50 Daphnia: 65 mg/l

Fattyalcohol ethoxylates > 5EO  
48 h LC50 Daphnia: 5.33 mg/l

propan-2-ol  
LC50 Daphnia magna (Water flea): > 10,000 mg/l

**12.2 Persistence and degradability**

**Product**

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

**Components**

Biodegradability : monoethanolamine  
Result: Readily biodegradable.

Fattyalcohol ethoxylates > 5EO  
Result: Readily biodegradable.

2-(2-butoxyethoxy)ethanol  
Result: Readily biodegradable.

fatty acids, coco, compds. with ethanolamine  
Result: no data available

potassium carbonate  
Result: Not applicable - inorganic

Fattyalcohol ethoxylates > 5EO  
Result: Readily biodegradable.

propan-2-ol  
Result: Readily biodegradable.

alcohols, c13-15-branched and linear, butoxylated ethoxylated  
Result: Readily biodegradable.

**Regain Floor**

**12.3 Bioaccumulative potential**

no data available

**12.4 Mobility in soil**

no data available

**12.5 Results of PBT and vPvB assessment**

**Product**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

no data available

**Section: 13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**13.1 Waste treatment methods**

- Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

**Section: 14. TRANSPORT INFORMATION**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

**Land transport (ADR/ADN/RID)**

- 14.1 UN number : 2491
- 14.2 UN proper shipping name : ETHANOLAMINE, SOLUTION
- 14.3 Transport hazard : 8

**Regain Floor**

class(es)  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None

**Air transport (IATA)**

14.1 UN number : 2491  
14.2 UN proper shipping name : Ethanolamine solution  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None

**Sea transport (IMDG/IMO)**

14.1 UN number : 2491  
14.2 UN proper shipping name : ETHANOLAMINE SOLUTION  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

**Section: 15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Non-ionic surfactants

**National Regulations**

**Take note of Dir 94/33/EC on the protection of young people at work.**

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.  
The Control of Substances Hazardous to Health Regulations.  
Health and Safety at Work Act.

**15.2 Chemical Safety Assessment**

This product contains substances for which Chemical Safety Assessments are still required.

**Section: 16. OTHER INFORMATION**

**Full text of H-Statements**

**Regain Floor**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

**Regain Floor**

materials or in any process, unless specified in the text.

**ANNEX: EXPOSURE SCENARIOS**

**DPD+ Substances:**

The following substances are the lead substances that contribute to the mixture Exposure Scenario according to the DPD+ Rule:

Route	Substance	CAS-No.	EINECS-No.
Ingestion	monoethanolamine	141-43-5	205-483-3
Inhalation	propan-2-ol	67-63-0	200-661-7
Dermal	monoethanolamine	141-43-5	205-483-3
Eyes	Fattyalcohol ethoxylates > 5EO	69227-22-1	
aquatic environment	No lead substance		

**Physical properties DPD+ Substances:**

Substance	Vapour pressure	Water solubility	Pow	Molar Mass
monoethanolamine	0.488 hPa	> 1,000 g/l	0.117	
propan-2-ol	6,020 Pa			60.10 g/mol

To calculate if your downstream Operating Conditions and Risk management Measures are safe, please calculate your risk factor at the website below:

[www.ecetoc.org/tra](http://www.ecetoc.org/tra)

**Short title of Exposure Scenario** : **Floor cleaner. Manual process**

**Use descriptors**

- Main User Groups : Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Sectors of end-use : **SU22:** Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Process categories : **PROC10:** Roller application or brushing  
**PROC8a:** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
- Product categories : **PC35:** Washing and cleaning products (including solvent based products)
- Environmental Release Categories : **ERC8a:** Wide dispersive indoor use of processing aids in open systems



**Regain Floor**