



SAFETY DATA SHEET

BLACKBOARD PAINT

Page 1
Issued: 01/03/04
Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: BLACKBOARD PAINT
Product code: B052/02/-
Company name: Glixtone Ltd.
Blackfriars Road
Nailsea
Bristol
BS48 4DJ
Tel: 01275 854911
Fax: 01275 858108

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),
HYDRODESULPHURIZED HEAVY 30-50%
EINECS: 265-185-4 CAS: 64742-82-1
[-] R10; [N] R51/53; [Xn] R65

3. HAZARDS IDENTIFICATION

Main hazards: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Flammable. May cause sensitisation by inhalation and skin contact. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and pain.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Wash affected skin thoroughly with soap and water or a proprietary skin cleanser. If irritation persists consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If symptoms persist, seek medical attention.

[cont...]

SAFETY DATA SHEET
BLACKBOARD PAINT**5. FIRE-FIGHTING MEASURES**

Extinguishing media: Carbon dioxide. Dry chemical powder. Do not use water.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Wear suitable protective clothing. Ensure good ventilation. Avoid breathing vapour. Avoid contact with skin and eyes.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Absorb in vermiculite, dry sand or earth and place into containers. Dispose of In Accordance With Local Authority Regulations

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Should not be necessary under normal conditions of use. If ventilation is not sufficient wear suitable respiratory equipment. If spraying wear suitable respiratory protective equipment.

Hand protection: Protective gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Black

Odour: Characteristic odour

Viscosity: Viscous

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS**

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SAFETY DATA SHEET
BLACKBOARD PAINT**14. TRANSPORT INFORMATION****ADR / RID**

UN no: 1263 **ADR Class:** 3
Packing group: III **Classification code:** F1
Shipping name: PAINT
Labelling: 3 **Hazard ID no:** 30

**IMDG / IMO**

UN no: 1263 **Class:** 3
Packing group: III **EmS:** F-E,S-E
Marine pollutant: YES **Labelling:** 3

IATA / ICAO

UN no: 1263 **Class:** 3
Packing group: III **Packing instructions:** 309(P&CA); 310(CAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Dangerous for the environment.



Risk phrases: R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10: Flammable.

R42/43: May cause sensitisation by inhalation and skin contact.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour

S24/25: Avoid contact with skin and eyes.

S29/56: Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

S36/37: Wear suitable protective clothing and gloves.

S51: Use only in well-ventilated areas.

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

SAFETY DATA SHEET
BLACKBOARD PAINT

Precautionary phrases: Contains 2-butanone oxime, cobalt salt. May produce an allergic reaction.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.