



**HOLCHEM**  
**SAFETY DATA SHEET**  
**CHLORFOAM SMS**

According to Regulation (EC) No. 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures.

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name** CHLORFOAM SMS

**Product number** HLC81

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Detergent. For professional use only.

**Uses advised against** Not for direct contact with Food or Beverage stuffs. Must not be used where acid based chemicals are present. Not for oral consumption.

**1.3. Details of the supplier of the safety data sheet**

**Supplier** Holchem Laboratories Limited  
 Gateway House, Pilsworth Road,  
 Pilsworth Industrial Estate,  
 Bury, Lancashire (UK)  
 BL9 8RD  
 +44 (0) 1706 222288  
 +44 (0) 1706 221550  
 info@holchem.co.uk

**1.4. Emergency telephone number**

**Emergency telephone** Out of Office Hours Emergency Information:-  
 For accidents and spillages involving this product that pose a threat to the environment, or human health, or require immediate first aid advice call:- +44(0) 7050 265597.  
 Note:- This number will not accept order queries or calls dealing with equipment breakdowns.  
 This product is registered with the NPIS. Irish Environmental Protection Agency 1890 335599  
 (This is a Lo Call Number) UK Environment Agency 24hour Advisory Service 0800 807060.

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**

**Physical hazards** Met. Corr. 1 - H290

**Health hazards** Skin Corr. 1B - H314 Eye Dam. 1 - H318

**Environmental hazards** Aquatic Acute 1 - H400 Aquatic Chronic 3 - H412

**2.2. Label elements**

**Pictogram**



## CHLORFOAM SMS

<b>Signal word</b>	Danger
<b>Hazard statements</b>	H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H400 Very toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P234 Keep only in original container. P273 Avoid release to the environment. P280 Wear protective clothing, gloves, eye and face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P313 Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
<b>Supplemental label information</b>	EUH031 Contact with acids liberates toxic gas.
<b>Contains</b>	DISODIUM METASILICATE, SODIUM HYPOCHLORITE SOLUTION, SODIUM ALKYL ETHER SULPHATE
<b>Detergent labelling</b>	< 5% anionic surfactants, < 5% chlorine-based bleaching agents, < 5% non-ionic surfactants, < 5% phosphates, < 5% phosphonates, < 5% polycarboxylates
<b>Supplementary precautionary statements</b>	P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P404 Store in a closed container.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>DISODIUM METASILICATE</b>	<b>1-5%</b>
CAS number: 6834-92-0	EC number: 229-912-9
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Met. Corr. 1 - H290	C;R34 Xi;R37
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
STOT SE 3 - H335	

## CHLORFOAM SMS

<b>SODIUM HYPOCHLORITE SOLUTION</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 7681-52-9	EC number: 231-668-3	REACH registration number: 01-2119488154-34
M factor (Acute) = 10		
<b>Classification</b> Met. Corr. 1 - H290 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Aquatic Acute 1 - H400 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> C;R34 R31 N;R50	
<b>POTASSIUM DECANOATE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 13040-18-1	EC number: 235-910-9	
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xi;R36/37/38.	
<b>POTASSIUM OCTANOATE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 764-71-6	EC number: 212-130-7	
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xi;R36/37/38.	
<b>SODIUM ARYL SULPHONATE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 1300-72-7	EC number: 215-090-9	REACH registration number: 01-2119513350-56-XXXX
<b>Classification</b> Eye Irrit. 2 - H319	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xi; R36	
<b>SODIUM ALKYL ETHER SULPHATE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 68891-38-3	EC number: 500-234-8	REACH registration number: 01-2119488639-16
<b>Classification</b> Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xi; R38, R41	

## CHLORFOAM SMS

<b>ALKYL DIMETHYL AMINE OXIDE</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 308062-28-4	EC number: 931-292-6	REACH registration number: 01-2119490061-47
M factor (Acute) = 1		
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Acute Tox. 4 - H302	Xn; R22. Xi; R38, R41. N; R50/53	
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
Aquatic Acute 1 - H400		
Aquatic Chronic 2 - H411		

  

<b>1-DODECANOL</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 112-53-8	EC number: 203-982-0	REACH registration number: 01-2119485976-15
M factor (Acute) = 1		
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Eye Irrit. 2 - H319	Xi; R36. N; R50.	
Aquatic Acute 1 - H400		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments** To the best of our knowledge, all of the substances used in this product are being supported for the relevant application in REACH. Note:- Sodium Hypochlorite content expressed as % Available Chlorine in Solution. Note:- H290 "May be Corrosive to Metals" refers to the neat product.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	When it is safe to do so, remove victim immediately from source of exposure. However, consideration should be given as to whether moving the victim will cause further injury.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Do not induce vomiting. Get medical attention. Rinse mouth thoroughly with water. Place unconscious person on the side in the recovery position and ensure breathing can take place.
<b>Skin contact</b>	Remove contaminated clothing that is not stuck to the skin. Flush area with clean water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** Neat product may cause chemical burns and permanent eye damage. Dilute product may cause irritation to the skin and eyes.

## CHLORFOAM SMS

<b>Inhalation</b>	Inhalation of neat product is unlikely. However, inhalation of mists or vapours of diluted product may result in soreness, irritation or burns to the mouth, nose and respiratory tract. If mixed with acid products Chlorine Gas may be evolved, this can result in irritation to eyes and difficulty in breathing. If inhaled this may result in irritation to the mouth nose and respiratory tract.
<b>Ingestion</b>	Unlikely route of exposure without deliberate abuse. If dilute chemical is ingested, soreness of mouth, throat and GI tract may occur together with redness and blistering. If neat chemical is ingested, chemical burning of mouth, throat and GI tract will occur.
<b>Skin contact</b>	May cause serious chemical burns to the skin.
<b>Eye contact</b>	May result in permanent eye damage.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Rinse well with water to neutral pH. If mixed with acidic material will produce Chlorine Gas, check for respiratory disorders.
-----------------------------	--

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** The product is non-combustible. Use fire-extinguishing media suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** This product is non combustible, on heating corrosive vapours may be formed. In contact with some metals (Aluminium, Zinc and their Alloys) Hydrogen Gas is formed, which may form an explosive mixture with air. Note - Comment refers to neat product. Contact with acids will generate toxic chlorine gas.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Protective clothing and respiratory protection should be worn when tackling fires involving this product. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Avoid or minimise the creation of any environmental contamination.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. For waste disposal, see Section 13. Absorb in vermiculite, dry sand or earth and place into containers. Dike far ahead of larger spills for later disposal.

### 6.4. Reference to other sections

**Reference to other sections** See sections 8,12 & 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## CHLORFOAM SMS

**Usage precautions**                      Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Read and follow manufacturer's recommendations.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions**                      Store in tightly-closed, original container in a well-ventilated place. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Store between 5 and 30 Degrees C. Store away from the following materials: Acids.

### 7.3. Specific end use(s)

**Specific end use(s)**                      Detergent, refer to Product Information Sheet for full details.

**Usage description**                      This product is suitable for cleaning food process plants, it is not suitable for direct food contact.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

**Ingredient comments**                      Where an exposure level is quoted, a risk assessment should consider if there is a need to monitor the atmosphere of the working environment. Results should be compared against the WEL and/or DNEL information provided. DNEL and/or PNEC information is supplied by manufacturers of substances in accordance with REACH legislation (Regulation (EC) No 1907/2006) , and is used to provide suitable risk reduction measures to limit exposure of the user of the substance to a non hazardous level. If the measured level of exposure by a route divided by the DNEL for the route is greater than 1, then further exposure controls should be implemented as described in section 8.2. Where new information becomes available under REACH, this will be passed on as revisions to the Safety Data Sheet. Where a worker is exposed to levels approaching a limit, further exposure control measures should be considered to reduce exposure to the substance. Where no Short Term WEL exists, guidance from the HSE is to use a value of three times the Long Term WEL. The WEL limits are laid down in the EH40 list as supplied by the HSE. This is taken from the Chemical Agents Directive (98/24/EC). The Long Term WEL refers to total exposure of a worker to a specific substance averaged out over an 8 hour period. The Short Term WEL refers to a single exposure of a worker to a specific substance over a 15 minute period. If the Short Term WEL is exceeded and no Long Term Limit is set, further exposure during the working shift is not permitted. Further controls should be implemented to ensure that future exposure to the substance is reduced below the levels set before the activity is repeated/continued.

#### SODIUM HYPOCHLORITE SOLUTION (CAS: 7681-52-9)

<b>DNEL</b>	Industry - Inhalation; Long term systemic effects: 1.55 mg/m <sup>3</sup> Industry - Dermal; Long term local effects: 0.5% wt/wt Industry - Inhalation; Long term local effects: 1.55 mg/m <sup>3</sup> Industry - Inhalation; Short term local effects: 3.1 mg/m <sup>3</sup> Industry - Inhalation; Short term systemic effects: 3.1 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 30 ug/l - Sediment (Freshwater); 0.21 ug/l - Sediment; 0.042 ug/l - Intermittent release; 0.26 ug/l

#### SODIUM ARYL SULPHONATE (CAS: 1300-72-7)

## CHLORFOAM SMS

**DNEL**  
Workers - Dermal; Long term systemic effects: 136.25 mg/kg/day  
Workers - Inhalation; Long term systemic effects: 26.9 mg/m<sup>3</sup>  
Workers - Dermal; Long term local effects: 0.096 mg/cm<sup>2</sup>  
General population - Inhalation; Long term systemic effects: 6.6 mg/m<sup>3</sup>  
General population - Dermal; Long term systemic effects: 68.1 mg/kg  
General population - Dermal; Long term local effects: 0.048 mg/cm<sup>2</sup>  
General population - Oral; Long term systemic effects: 3.8 mg/kg/day

**PNEC**  
- Fresh water; 0.23 mg/l  
- Marine water; 0.023 mg/l  
- Intermittent release; 2.3 mg/l  
- Sediment, Fresh water; 0.862 mg/kg  
- Sediment, Marine water; 0.0862 mg/kg  
- Soil; 0.037 mg/kg  
- STP; 100 mg/l

### SODIUM ALKYL ETHER SULPHATE (CAS: 68891-38-3)

**DNEL**  
Professional - Dermal; Long term systemic effects: 2750 mg/kg/day  
Professional - Inhalation; Long term systemic effects: 175 mg/m<sup>3</sup>  
General population - Oral; Long term systemic effects: 15 mg/kg/day  
General population - Dermal; Long term systemic effects: 1650 mg/kg/day  
General population - Inhalation; Long term systemic effects: 52 mg/m<sup>3</sup>

**PNEC**  
- Fresh water; 0.24 mg/l  
- Marine water; 0.024 mg/l  
- Intermittent release; 0.071 mg/l  
- Sediment (Freshwater); 5.45 mg/kg  
- Sediment (Marinewater); 0.545 mg/kg  
- Soil; 0.946 mg/kg  
- STP; 10 g/l

### SODIUM C14-C17 SECONDARY ALKYL SULPHONATE (CAS: 97489-15-1)

**DNEL**  
Professional - Dermal; Short term local effects: 2,8 mg/cm<sup>2</sup>  
Professional - Dermal; Long term systemic effects: 5mg/Kg bw/day  
Professional - Inhalation; Long term systemic effects: 35mg/m<sup>3</sup>  
- Dermal; Long term local effects: 2.8 mg/cm<sup>2</sup>

**PNEC**  
- Intermittent release; 0.06mg/l  
- Soil; 9.4mg/Kg dw  
- Sediment (Marinewater); 0.94 mg/kg dw  
- Fresh water; 0.04mg/l  
- Marine water; 0.004mg/l  
- STP; 600mg/l  
- Sediment (Freshwater); 9.4 mg/Kg dw

### ALKYL DIMETHYL AMINE OXIDE (CAS: 308062-28-4)

**DNEL**  
Professional - Dermal; Long term systemic effects: 11 mg/kg/day  
Professional - Inhalation; Long term systemic effects: 15.5 mg/m<sup>3</sup> 8h  
Professional - Dermal; Long term local effects: 0.27 %  
General population - Dermal; Long term systemic effects: 5.5 mg/kg/day  
General population - Inhalation; Long term systemic effects: 3.8 mg/m<sup>3</sup>  
General population - Oral; Long term systemic effects: 0.44 mg/kg/day

## CHLORFOAM SMS

### PNEC

- Fresh water; 0.0335 mg/l
- Marine water; 0.00335 mg/l
- Intermittent release; 0.0335 mg/l
- Sediment (Freshwater); 1.02 mg/kg
- Sediment (Marinewater); 24 mg/kg
- Soil; 1.02 mg/kg
- STP; 24 mg/kg

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

#### Personal protection

The PPE indicated above is not a COSHH assessment. It represents PPE that should be considered during the manufacture, distribution, use and final disposal stages of this product's life cycle. It is the responsibility of employers to conduct a COSHH/risk assessment to determine appropriate PPE levels. The information given below should be used to support this assessment. Where possible replace manual processes with automated or closed processes to minimise contact with the product.

#### Eye/face protection

The following protection should be worn: Refer to EN Standard 166 to select appropriate level of protection. Full face visor or shield.

#### Hand protection

Rubber (natural, latex). Polyvinyl chloride (PVC). Refer to Standard EN 374. Neoprene.

#### Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Reference to EN 13832 and EN 943 is useful when selecting footwear and clothing.

#### Hygiene measures

Promptly remove non-impervious clothing that has become contaminated, provided it is not adhered to the skin. Contaminated clothing and shoes must be discarded. Provide eyewash station and safety shower.

#### Respiratory protection

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Workplace Exposure Limit. In the case of dust or aerosol formation (eg spraying), or vapour from hot vessels, use respiratory protection with an approved filter Type B(P3).

#### Environmental exposure controls

Do not allow the substance to contaminate surface water/ground water. See points 6, 12 & 13. Discharge of solutions into effluent systems (including municipal drains) or to surface water are expected to cause significant pH changes. Discharge of solutions should be carried out such that pH changes are minimised. Where necessary pH buffering measures should be adopted. Users of this product should consult local drainage and permitting authorities to ensure that any restrictions or discharge consents are adhered to.

#### General Health and Safety Measures.

A full Risk Assessment should be carried out before handling any chemical(s). Risk Assessments should refer to COSHH, and any other relevant legislation or industry specific guidelines governing the use of chemicals. In use solutions are likely to have extreme pH values and should be considered to be classified as H314. This should be considered when selecting control measures and PPE.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

##### Appearance

Clear liquid.

**CHLORFOAM SMS**

<b>Colour</b>	Colourless to pale yellow.
<b>Odour</b>	Bleach
<b>Odour threshold</b>	Not applicable.
<b>pH</b>	pH (diluted solution): 11.0 - 12.0 @ 1%
<b>Melting point</b>	Not applicable.
<b>Initial boiling point and range</b>	Not applicable.
<b>Flash point</b>	Not applicable. Contains no Flammable Components
<b>Evaporation rate</b>	Not applicable.
<b>Evaporation factor</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	Not applicable.
<b>Vapour pressure</b>	Not applicable.
<b>Vapour density</b>	Not applicable.
<b>Relative density</b>	1.15 @ 20 Degrees C
<b>Bulk density</b>	Not applicable.
<b>Solubility(ies)</b>	Completely soluble in water
<b>Partition coefficient</b>	Technically not feasible.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Decomposition Temperature</b>	Not applicable.
<b>Viscosity</b>	Not determined.
<b>Explosive properties</b>	Not applicable.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising. Contains Sodium Hypochlorite. This has oxidising properties.
<b><u>9.2. Other information</u></b>	
<b>Refractive index</b>	Not applicable.
<b>Particle size</b>	Not applicable.
<b>Molecular weight</b>	Not applicable.
<b>Volatility</b>	Not applicable.
<b>Saturation concentration</b>	Not applicable.
<b>Critical temperature</b>	Not applicable.
<b>Volatile organic compound</b>	Not applicable.
<b>Explosive Properties</b>	Not Classified as Explosive
<b>Storage Temperature Range</b>	+5 to +30 Degrees

## CHLORFOAM SMS

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** Not expected to react when correctly stored and used. Mixing with other chemicals may produce unexpected reactions.

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended. - See note 10.6. Decomposes over time to produce Oxygen and Sodium Chloride.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Refer to section 10.1.

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid excessive heat for prolonged periods of time. Generates toxic gas in contact with acid.

#### 10.5. Incompatible materials

**Materials to avoid** Reaction with acids will produce toxic Chlorine Gas. - Note: reaction relates to neat product. In contact with cellulose based material such as wood or paper a potential for ignition and slow burning exists. Reaction with Aluminium, Zinc, Tin, Copper or their alloys produces flammable Hydrogen Gas.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Will evolve Hydrogen Gas when in contact with soft metals such as Aluminium. Will evolve Chlorine Gas in contact with Acids. Natural decay (especially in warm conditions or in direct sunlight) will evolve Oxygen Gas.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

**ATE oral (mg/kg)** 54,352.27

##### Skin sensitisation

**Skin sensitisation** There is no evidence of skin sensitisation in humans.

##### Carcinogenicity

**Carcinogenicity** The components of this formulation will not be systemically available in the body under normal conditions of handling. As a consequence it is not expected to cause cancer.

##### Reproductive toxicity

**Reproductive toxicity - fertility** The components of this formulation will not be systemically available in the body under normal conditions of use and handling. As a consequence it is not expected to be toxic to the reproductive system or developing foetus.

##### General information

See section 4.2.

##### Inhalation

Unlikely route of exposure. Inhalation of sprayed droplets may result in soreness of the throat, mouth and nose. - See section 4.2. Mixing with acid will evolve toxic Chlorine Gas.

##### Ingestion

May cause chemical burns in mouth, oesophagus and stomach.

##### Skin contact

Causes severe burns.

##### Eye contact

Risk of serious damage to eyes. May cause permanent eye injury.

## CHLORFOAM SMS

### SECTION 12: Ecological Information

**Ecotoxicity** This product is classified as very toxic to aquatic life, this refers to the neat product. Normal use is not expected to pose a risk.

#### 12.1. Toxicity

**Toxicity** Normal use is not expected to pose an ecological risk.

#### 12.2. Persistence and degradability

**Persistence and degradability** The surfactant(s) used in this preparation complies (comply) with the biodegradability criteria as laid down in the European Detergents Regulation No 648/2004 as amended.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Not expected to bioaccumulate.

**Partition coefficient** Technically not feasible.

#### 12.4. Mobility in soil

**Mobility** The product contains substances which are water soluble and may spread in water systems.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** Not determined.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be considered. Do not mix with other chemicals.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

#### 14.1. UN number

**UN No. (ADR/RID)** 1719

**UN No. (IMDG)** 1719

**UN No. (ICAO)** 1719

**UN No. (ADN)** 1719

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS DISODIUM METASILICATE, SODIUM HYPOCHLORITE SOLUTION)

**Proper shipping name (IMDG)** CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS DISODIUM METASILICATE, SODIUM HYPOCHLORITE SOLUTION, ALKYL DIMETHYL AMINE OXIDE, 1-DODECANOL)

**Proper shipping name (ICAO)** CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS DISODIUM METASILICATE, SODIUM HYPOCHLORITE SOLUTION)

**Proper shipping name (ADN)** CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS DISODIUM METASILICATE, SODIUM HYPOCHLORITE SOLUTION)

## CHLORFOAM SMS

### 14.3. Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C5
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

#### Transport labels



### 14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS	F-A, S-B
ADR transport category	2
Emergency Action Code	2R
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>EU legislation</b>	European Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures. This replaces Directive 67/548/EEC - Classification, Packaging and Labelling of Dangerous Substances and Regulation (EC) No. 453/2010 relating to the Classification, Packaging and Labelling of Dangerous Preparations. Also considered is the REACH Regulation (EC) No.1907/2006.
-----------------------	---

## CHLORFOAM SMS

### 15.2. Chemical safety assessment

#### Pcs Information

No chemical safety assessment has been carried out.

<b>SECTION 16: Other information</b>
--------------------------------------

<b>Abbreviations and acronyms used in the safety data sheet</b>	<p>(EC) No. 1272/2008 : EU Regulation on Classification, Labelling and Packaging of Substances and Mixtures.</p> <p>NPIS - National Poisons Information Service.</p> <p>vPvB - Very Persistent, Very bioaccumulative.</p> <p>PBT - Persistent, Bioaccumulative &amp; Toxic.</p> <p>REACH - Registration, Evaluation, Authorisation &amp; restriction of CHemicals (Regulation EC 1907/2006).</p> <p>DNEL - Derived No Effect Limit.</p> <p>PNEC - Predicted No Effect Concentration.</p> <p>COSHH - Control of Substances Hazardous to Health.</p> <p>NOEC - No Observed Effect Concentration.</p> <p>NOAEL - No Observable Adverse Effect Level.</p> <p>LC50 - Lethal Concentration 50 - The environmental contamination at which 50% mortality is reached over a fixed time scale.</p> <p>EC50 - Effective Concentration 50 - Concentration of a substance in water at which 50% of the maximum biological response is reached.</p> <p>Industry - Refers in section 8 to application of the substance in an industrial process.</p> <p>Professional - Refers in section 8 to application/use of the preparation/product in a skilled trade premises.</p>
<b>General information</b>	<p>This document is a Safety Data Sheet, NOT a CoSHH assessment. It is the customer's responsibility to conduct a full CoSHH assessment, taking into account the information held within this document along with other local factors considered in a risk assessment. The Risk and Hazard statements listed below are the full text of abbreviations used in this document. They are not the final classification, for this refer to section 2.</p>
<b>Revision comments</b>	Formulation and SDS review with no change in classification
<b>Revision date</b>	23/11/2017
<b>SDS number</b>	25305
<b>Risk phrases in full</b>	<p>R31 Contact with acids liberates toxic gas.</p> <p>R34 Causes burns.</p> <p>R35 Causes severe burns.</p> <p>R36 Irritating to eyes.</p> <p>R36/37/38 Irritating to eyes, respiratory system and skin.</p> <p>R36/38 Irritating to eyes and skin.</p> <p>R37 Irritating to respiratory system.</p> <p>R38 Irritating to skin.</p> <p>R41 Risk of serious damage to eyes.</p> <p>R50 Very toxic to aquatic organisms.</p>

## CHLORFOAM SMS

### Hazard statements in full

H290 May be corrosive to metals.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

### REACH extended MSDS comments

REACH requires that persons handling chemicals should take the necessary risk management measures, in accordance with assessments from manufacturers and importers of chemical substances. The relevant recommendations must be passed along the supply chain. These assessments are generally reported in Exposure Scenarios. Where Exposure Scenarios have been provided for substances used in this product, the relevant information is incorporated into the safety data sheet.

### END OF SAFETY DATA SHEET

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.