

Lime-A-Way Extra



Heavy Duty Delimer



- concentrated, acidic formulation lifts even the heaviest lime scale deposits
- suitable for deliming commercial dishmachines
- regular use in hard water areas, maintains maximum efficiency of dishmachines
- odourless formulation – pleasant to use
- should not be used on copper, zinc alloys and porous enamel or marble surfaces



Lime-A-Way Extra

Heavy Duty Delimer

This premium Ecoguard product offers maximum hygiene at lowest cost.

Lime-A-Way Extra is directly dispensed from its ready-to-use jug.

Maximum Machine Efficiency:

Lime build up in commercial dishmachines reduces washing and rinse efficiency and increases energy costs. Regular use of Lime-A-Way Extra according to manufacturer's instructions maintains optimum efficiency.

Use Instructions:

To descale a dishmachine:

1. Switch off the air extraction.
 2. Ensure that during descaling no detergent is dosed into the dishmachine (e.g. switch off dosing system or remove capsule).
 3. Remove kitchenware and drain the dishmachine.
 4. Refill the machine with water and add between 8 – 22 ml/l of Lime-A-Way Extra.
 5. In case of heavy lime build-up in the rinse section, use Lime-A-Way Extra undiluted with the sprayer.
 6. Let product work a few minutes.
 7. Start the machine. Depending on lime scale-up runtime of the machine should be 10 to 30 minutes.
 8. Stop and drain the machine. Take a water hose to thoroughly rinse down the parts which have been sprayed with undiluted product.
 9. Refill the machine with clean water.
 10. Start machine, let run a short time, then switch the detergent dosage system and air extraction on again.
- Do not breath in the aerosols, only use the approved sprayer. Contact your Ecolab for further usage instructions.

Ingredients:

Declaration acc. to recommendation 89/542/EEC: <5%: nonionic surfactants.
Further ingredients: phosphoric acid, dye, defoamer.

Safety:

Corrosive product. For further instructions see product label and safety data sheet!

Pack Size:

4 x 5l per outercase

Storage Conditions:

Keep at a temperature between 10° and 35°C.
Do not mix with any other product.
Keep out of reach of children.



APPROVED

RIS 0Z0000000A

APPROVED AFTER CORRECTIONS

COUNTRY _____

DATE / NAME _____

PRINT-OUT NOT IN ORIGINAL SIZE!

Lime-A-Way Extra / GB

Catsheet
210 x 297 mm

CPS / 13.02.2003

Cyan Magenta Yellow Black

CS_Lime-A-Way_Extra_GB

LAWECGX.pdf